

SUPPLY SPECIFICATION SHEET

Magnetic sheeting
Barrium Magnet material
Date : 2022-2-11

Size

1. 30m × 615 × 0.40mm/MUV/2.0mm Pole pitch/Matte white pvc (total 0.5mm)
2. 15m × 1270 × 0.40mm/MUV/2.0mm Pole pitch/Matte white pvc (total 0.5mm)
3. 15m × 615 × 0.65mm/MUV/2.0mm Pole pitch/Matte white pvc (total 0.75mm)
4. 15m × 1270 × 0.65mm/MUV/2.0mm Pole pitch/Matte white pvc (total 0.75mm)
5. 30m × 615 × 0.5mm/MUV/2.0mm Pole pitch (Plain brown)
6. 15m × 1270 × 0.75mm/MUV/2.0mm Pole pitch (Plain brown)

Dimensions & Tolerance

Item	Length (m)		Width (mm)		Thickness (mm)				Thickness of PVC (mm)
	30	15	615	1270	0.4	0.5	0.65	0.75	
Size	30	15	615	1270	0.4	0.5	0.65	0.75	0.1~0.13
Tolerance	0/+0.6	0/+0.6	-1/+3	-1/+5	±0.04	±0.05	±0.05	±0.05	

Pull Strength

Code	Thickness (mm)	Pole pitch (mm)	Pull (g/cm ²)
--	0.40	2.0	≥13
--	0.50	2.0	≥19
--	0.65	2.0	≥25
--	0.75	2.0	≥30

Storage

In the surrounding temperature -20°C to +70°C within the scope of the normal work

Storage Condition: 25°C and 50% humidity conditions

Shelf life: 12 months under original packaging condition

The magnetic force is permanent and will not degrade in normal temperature without strong magnetic interference.